



Features

8-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, also the Auto fan speed, Turbo Mode, 3D Air Flow: Vertical/Horizontal Auto Swing, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling -15°C, Low Temperature Heating (-20°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Gentle cooling, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, Wi-Fi, Built-in Bipolar Ionic Generator (BIG), UVC Sterilization, Special Coating, Hidden Display, Self-cleaning, Healthy Filter, Sleep Mode, Breeze away, ECO, Timer, GEN mode, New AI Algorithm, Aroma Module

Capacity			12000BTU	
Rated volt and frequency		V/Hz	220-240V~/50HZ	
Mode			Cooling Heating	
Rated capacity	W	3580(1000~4000)	3900(1000~4500)	
Power input	W	792(290~1500)	944(290~1830)	
Current input	A	3.6(1.5~9.0)	4.6(1.5~10.0)	
SEER / Energy Class			9,4 A+++ /	
SCOP / Energy Class - average			/ 5,1/A+++	
SCOP / Energy Class - warmer			/ 5,8/A+++	
Operating range (°C)		°C	15~53 -25~30	
Energy consumption (per year, based on standard test results)		kWh	131 /	
Energy consumption (per year, based on standard test results) - average		kWh	/ 742	
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 894	
Dehumidifying		Kg/h	1,5	
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4	
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I	
Max. input consumption		W	1830	
Max. current		A	10	
Compressor		Model	KSN98D64UEZ3	
		Type	Rotary	
		Brand	GMCC	
Indoor	Indoor Air Circulation	m ³ /h	860	
	Indoor Noise Level dB	dB(A)	56/50/45/42/39/36/33	
	Net Dimension	mm	909×305×209	
	Packing Dimension	mm	981×375×275	
	Net Weight / Gross Weight	Kg	10,4/13,2	
Outdoor	Outdoor Noise Level dB	dB(A)	64	
	Net Dimension	mm	853×602×349	
	Packing Dimension	mm	890×628×385	
	Net Weight / Gross Weight	Kg	30/32	
	Refrigerant Type		R32	
	Refrigerant Weight	Kg	0,85	
	GWP		675	
	tCO₂eq.		0,57	
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5	
Refrigerant piping		Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-3/8)
		Max. refrigerant pipe length / Max. difference in level	m	25/10