



Features

8-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, also the Auto fan speed, Turbo Mode, 3D Air Flow: Vertical/Horizontal Auto Swing, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling -15°C, Low Temperature Heating (-20°C), Comfortable Cooling, Independent Dehumidification, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Gentle cooling, Intelligent defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Leakage Detection, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, Wi-Fi, Built-in Bipolar Ionic Generator (BIG), UVC Sterilization, Special Coating, Hidden Display, Self-cleaning, Healthy Filter, Sleep Mode, Breeze away, ECO, Timer, GEN mode, New AI Algorithm, Aroma Module

Capacity			18000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling Heating
Rated capacity		W	5260(1250~5920) 5410(1250~6090)
Power input		W	1560(330-2350) 1392(340-2550)
Current input		A	7.1(1.7~12.0) 6.4(1.7~13.0)
SEER / Energy Class			6,6/A++ /
SCOP / Energy Class - average			/ 4,1/A+
SCOP / Energy Class - warmer			/
Operating range (°C)		°C	17-53 -20-30
Energy consumption (per year, based on standard test results)		kWh	276 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 1366
Energy consumption (per year, based on standard test results) - warmer		kWh	/
Dehumidifying		Kg/h	1,8
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	2550
Max. current		A	13
Compressor	Model		C-4RZ120H3AAF
	Type		Rotary
	Brand		CRSS
Indoor	Indoor Air Circulation	m³/h	950
	Indoor Noise Level dB	dB(A)	57/54/50/45/40
	Net Dimension	mm	909×305×209
	Packing Dimension	mm	981×375×275
	Net Weight / Gross Weight	Kg	10,4/13,2
Outdoor	Outdoor Noise Level dB	dB(A)	64
	Net Dimension	mm	853×602×349
	Packing Dimension	mm	890×628×385
	Net Weight / Gross Weight	Kg	31/33
	Refrigerant Type		R32
	Refrigerant Weight	Kg	0,96
	GWP		675
	tCO ₂ eq.		0,65
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
Refrigerant piping		Liquid side / Gas side / Length	mm Dg4/Dg8(1/4-3/8)
		Max. refrigerant pipe length / Max. difference in level	m 25/10