



Features

I Feel / Follow me, Breeze away, Smart Air Flow, ECO, Super EMC performance, Self-diagnostic, Intelligent defrosting, Self-Cleaning Function, Anti-fungus Function, Anti-Rust Cabinet, Independent Dehumidification mode, Super Quiet Design, Low-noise airflow, Turbo mode, Auto mode, Sleep Mode, Fault Code Indication, Emergency button, Auto restart, Timer Auto turn off/on, 4-Fan Speed, Five speed outdoor fan motor, Mono & multi compatibility, 8°C heating feature, Low Temperature Heating/Cooling, Honeycomb filter, Washable filter, High density filter, Dual side Drainage, Stability Protection, 3D Air Flow, 56°C sterilization, Refrigerant Leakage Detect, Remote control, Louver position memory, Horizontal louver auto swing, Hidden led display, Display ON/OFF, Comfortable Cooling, Strong Cooling at 60°C, Rapid Cooling and Rapid Heating, Horizontal swing, RC holder, Hydrophilic Aluminum Fin, Backup Switch, Multi Fan Speed Equipped, I-clean, Top plate/cover, Auto Swing Louver function, Anti-Cold Air, Wi Fi, Additional Health filter, Tray Heater

Capacity			24000BTU
Rated volt and frequency		V/Hz	220-240V~/50Hz/1P
Mode			Cooling Heating
Rated capacity		W	6840(1830~7820) 7050(1850~7960)
Power input		W	2099(410~2800) 1900(420~3000)
Current input		A	9.8(2.3~13.0) 8.6(2.3~14.0/A+)
SEER / Energy Class			6,5/A++ /
SCOP / Energy Class - average			/ 4.0/A+
SCOP / Energy Class - warmer			/ 5,1/A+++
Operating range (°C)		°C	15-53 -20-30
Energy consumption (per year, based on standard test results)		kWh	366 /
Energy consumption (per year, based on standard test results) - average		kWh	/ 1995
Energy consumption (per year, based on standard test results) - warmer		kWh	/ 1537
Dehumidifying		Kg/h	1,8
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	3000
Max. current		A	14
Compressor		Model	
		Type	Rotary
		Brand	SANYO
Indoor	Indoor Air Circulation	m ³ /h	1100
	Indoor Noise Level dB	dB(A)	58/52/48/44/41
	Net Dimension	mm	1100×333×222
	Packing Dimension	mm	1165×405×295
	Net Weight / Gross Weight	Kg	14/17
Outdoor	Outdoor Noise Level dB	dB(A)	57
	Net Dimension	mm	920×699×380
	Packing Dimension	mm	960×732×400
	Net Weight / Gross Weight	Kg	40/43
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,11
	GWP		675
	tCO ₂ eq.		0,75
Max. Discharge / Max. Suction pressure		Mpa	3,7/1,2
Refrigerant piping	Liquid side / Gas side / Length	mm	Dg4/Dg8 (1/4-3/8)
	Max. refrigerant pipe length / Max. difference in level	m	25/10