



## Features

7-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, 5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Holder RC, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent Defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Cooling at 53°C, Refrigerant Leakage Detection, Compressor Preheating, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Sleep Mode, ECO, Timer, AI Energy Saving 2.0

<b>Capacity</b>		24000BTU	
<b>Rated volt and frequency</b>		V/Hz 220-240V~/50HZ	
<b>Mode</b>		<b>Cooling</b>	<b>Heating</b>
<b>Rated capacity</b>	W	7040(1500~7800)	7080(1500~7900)
<b>Power input</b>	W	2324(390~2800)	2178(390~3000)
<b>Current input</b>	A	10.5(1.8~12.6)	10.0(1.8~13.4)
<b>SEER / Energy Class</b>		6,4 A++	/
<b>SCOP / Energy Class - average</b>		/	4,0/A+
<b>SCOP / Energy Class - warmer</b>		/	5,1/A+++
<b>Operating range (°C)</b>		°C 15-52°C	-20-30°C
<b>Energy consumption (per year, based on standard test results)</b>		kWh 383	/
<b>Energy consumption (per year, based on standard test results) - average</b>		kWh /	1715
<b>Energy consumption (per year, based on standard test results) - warmer</b>		kWh /	1593
<b>Dehumidifying</b>		Kg/h 2	
<b>Degree of protection (IN) / (OUT)</b>		(IP) IPX0/IPX4	
<b>Class of electric protection (IN) / (OUT)</b>		Class I / Class II I/I	
<b>Max. input consumption</b>		W 3000	
<b>Max. current</b>		A 13,4	
<b>Compressor</b>		Model	C-6RZ146H3DBF
		Type	Rotary
		Brand	SANYO
<b>Indoor</b>	Indoor Air Circulation	m <sup>3</sup> /h	1000
	Indoor Noise Level dB	dB(A)	58/56/54/51/49/46/40
	Net Dimension	mm	1005×321.5×220
	Packing Dimension	mm	1096×390×297
	Net Weight / Gross Weight	Kg	11/13
<b>Outdoor</b>	Outdoor Noise Level dB	dB(A)	67
	Net Dimension	mm	920×699×380
	Packing Dimension	mm	949×732×392
	Net Weight / Gross Weight	Kg	38/40,5
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,14
	GWP		675
	tCO <sub>2</sub> eq.		0,77
<b>Max. Discharge / Max. Suction pressure</b>		Mpa	4.3/2.5
<b>Refrigerant piping</b>	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-1/2)
	Max. refrigerant pipe length / Max. difference in level	m	25/10