



Features

7-Fan Speed: Mute/Low/Low-Mid/Mid/Mid-High/High/Turbo, 5-Fan Speed: Mute/Low/Mid/High/Turbo, Turbo Mode, Anti-cold Air, Mute Mode, 8°C heating, I Feel, Low Temperature Cooling (-15°C), Comfortable Cooling, Independent Dehumidification, Holder RC, Auto Mode, Display On/Off, Smart Airflow, Rapid Cooling and Rapid Heating, Intelligent Defrost, Emergency Button, Rust Proof, Wide Voltage Range Start-up, Children Lock, Cooling at 53°C, Refrigerant Leakage Detection, Compressor Preheating, Auto-restart, Self-diagnosis, Backlight Display remote control, Louver Position Memory, Dual Drainage, Easy-washable Filter, I Set, Hidden Display, Self-cleaning, Self-cleaning (Outdoor unit), Sleep Mode, ECO, Timer, AI Energy Saving 2.0, Wi Fi, Ionizer Filter, 4D Air Flow, Horizontal Swing

Capacity			24000BTU
Rated volt and frequency		V/Hz	220-240V~/50HZ
Mode			Cooling
Rated capacity		W	7040(1500~7800)
Power input		W	2324(390~2800)
Current input		A	10.5(1.8~12.6)
SEER / Energy Class			6,4 A++
SCOP / Energy Class - average			/
SCOP / Energy Class - warmer			5,1/A+++
Operating range (°C)		°C	15-52°C
Energy consumption (per year, based on standard test results)		kWh	383
Energy consumption (per year, based on standard test results) - average		kWh	/
Energy consumption (per year, based on standard test results) - warmer		kWh	/
Dehumidifying		Kg/h	2
Degree of protection (IN) / (OUT)		(IP)	IPX0/IPX4
Class of electric protection (IN) / (OUT)		Class I / Class II	I/I
Max. input consumption		W	3000
Max. current		A	13,4
Compressor	Model		C-6RZ146H3DBF
	Type		Rotary
	Brand		SANYO
Indoor	Indoor Air Circulation	m³/h	1000
	Indoor Noise Level dB	dB(A)	58/56/54/51/49/46/40
	Net Dimension	mm	1005×321.5×220
	Packing Dimension	mm	1096×390×297
	Net Weight / Gross Weight	Kg	11/13
Outdoor	Outdoor Noise Level dB	dB(A)	67
	Net Dimension	mm	920×699×380
	Packing Dimension	mm	949×732×392
	Net Weight / Gross Weight	Kg	38/40,5
	Refrigerant Type		R32
	Refrigerant Weight	Kg	1,14
	GWP		675
	tCO ₂ eq.		0,77
	Max. Discharge / Max. Suction pressure	Mpa	4.3/2.5
	Liquid side / Gas side / Length	mm	Dg4/Dg8(1/4-1/2)
Refrigerant piping		Max. refrigerant pipe length / Max. difference in level	m
			25/10